# **IN THE CLAIMS:**

Please cancel claim 8 without prejudice to or disclaimer of the subject matter recited therein.

Please amend claims 1 and 13 as follows:

#### **LISTING OF CURRENT CLAIMS**

1. (Currently Amended) A system for multi-path simulation comprising: a signal generator for generating a signal;

an attenuating device coupled to the signal generator for attenuating the signal and generating an attenuated signal to simulate an attenuation resulting from a transmission of the signal;[[ and]]

a shielded anechoic chamber comprising:

an antenna coupled to the attenuating device for transmitting the attenuated signal, wherein the antenna can be shifted to simulate a phase shift between a direct path and a main indirect path of the system; and

a reflector for reflecting the attenuated signal to generate a reflected signal; and

a control unit coupled directly to the signal generator and the attenuating device for controlling a generation of the signal and adjusting an attenuating range of the attenuating device.

2. (Original) The system of claim 1, wherein the shielded anechoic chamber further comprises:

a communication device for receiving the attenuated signal and the reflected signal.

3. (Original) The system of claim 1, wherein the signal generator is a vector signal generator.

5

10

15

## Application No. 10/663,664

- 4. (Original) The system of claim 1, wherein the signal generator is a Golden Sample of the communication device.
- 5. (Original) The system of claim 1, wherein the attenuating device is a step attenuator.
  - 6. (Original) The system of claim 1, wherein the antenna is a dipole antenna.
- 7. (Original) The system of claim 1, wherein the antenna is deployed between the reflector and the communication device.

### Claim 8. (Canceled)

- 9. (Original) The system of claim 2, further comprising:
- a control unit coupled to the communication device for acquiring signal properties received by the communication device.
- 10. (Original) The system of claim 1, wherein the shielded anechoic chamber further comprises:
- a turntable for setting the communication device and changing a reception azimuth of the communication device.
- 11. (Original) The system of claim 1, wherein the shielded anechoic chamber further comprises:
  - a movable platform for setting and shifting the antenna.
- 12. (Original) The system of claim 1, wherein the communication device is deployed in a quiet zone of the shielded anechoic chamber.
  - 13. (Currently Amended) A method for multi-path simulation comprising: generating a signal utilizing a signal generator;

attenuating the signal to generate an attenuated signal for simulating an attenuation resulting from a transmission of the signal;

transmitting the attenuated signal by an antenna, wherein the antenna is located in a shielded anechoic chamber with a reflector, and the reflector reflects the

attenuated signal to generate a reflected signal;

receiving the attenuated signal and the reflected signal by a communication device located within the shielded anechoic chamber:

shifting the antenna to simulate a phase shift between a direct transmission path and a main indirect transmission path of the signal;[[ and]]

rotating[[ the]] <u>a</u> turntable to change a reception azimuth of the communication device; <u>and</u>

adjusting a position of the antenna and changing the phase shift between the direct transmission path and the main indirect transmission path of the signal utilizing a control unit coupled directly to the signal generator and the attenuating device.

- 14. (Original) The method of claim 13, wherein the signal is generated by a vector signal generator.
- 15. (Original) The method of claim 13, wherein the signal is generated by a Golden Sample of the communication device.
- 16. (Original) The method of claim 13, wherein the signal is attenuated by a step attenuator.
- 17. (Original) The method of claim 13, wherein the antenna is deployed between the reflector and the communication device.

#### Claims 18-19. (Canceled)

20. (Original) The method of claim 13, wherein the communication device is deployed in a quiet zone of the shielded anechoic chamber.

5

10

15

Application No. 10/663,664

Claims 21-29. (Canceled)